




CV

POLYETHYLENE TANKS FOR ABOVE GROUND



300 - 5.000



10.000 - 13.000



For drinking water

Suitable to contain liquids other than water, in compliance with the table of resistance (page 103)

For above ground use only

For use with chemicals, see the table of tank chemical resistance (page 103).

ELBI guarantees the resistance of PLASTO tanks to liquids declared suitable (R) in the table of tank resistance.

Maintenance of the characteristics of the liquids contained inside of PLASTO tanks should be checked by and is the responsibility of the user.

INSTALLATION IN SERIES:

Keep an adequate distance (min. 20-25 cm) between the tanks to enable them to dilate freely during the filling phase.

WARRANTY: 2 YEARS

Version without holes available.

DIMENSIONS

MODEL	CODE				DN1		NOTES
		LITRES	mm	mm		mm	
CV- 300	A510051	300	630	1170	1"	300	
CV- 500	A510055	500	700	1460	1"	300	
CV- 750	A510059	750	800	1680	1" 1/4	300	
CV- 1000	A510062	1000	800	2180	1" 1/4	300	
CV- 1500	A510067	1500	1060	1920	1" 1/2	300	
CV- 2000	A510070	2000	1200	2015	1" 1/2	400	
CV- 3000	A510074	3000	1470	2050	1" 1/2	400	
CV- 5000	A510080	5000	1790	2210	2"	400	
CV-10000 (•)	A510092	10000	2300	2650	-	600	
CV-13000 (•)	A510095	13000	2300	3400	-	600	

(•) Tanks exclusively produced in the factory in Limena (PD).