



### VARIABLE ARC NOZZLE (VAN) SERIES

Adjustable 1800™/UNI-Spray™ Series Nozzles  
Maximum flexibility to Save Time and Speed-Up installation

#### APPLICATIONS

These nozzles are ideal for watering irregularly shaped turf and shrub areas because it is easy to increase or decrease arc settings.

#### FEATURES

- Top Color-Coded™ for easy radius and arc identification
- Easy arc adjustment from 0 to 330° for 4, 6 and 8-VAN and 0 to 360° for 10, 12, 15 and 18-VAN
- Convenient re-sealable bags with separate, detachable nozzle and screen pouches

#### PERFORMANCE

##### 4-VAN Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
330°	1,0	0,9	0,14	189	218
	1,5	1,0	0,17	183	215
	2,0	1,2	0,20	152	176
	2,1	1,2	0,20	152	176
270°	1,0	0,9	0,12	198	229
	1,5	1,0	0,14	187	216
	2,0	1,2	0,16	148	171
180°	1,0	0,9	0,07	173	200
	1,5	1,0	0,09	180	208
	2,0	1,2	0,10	139	161
90°	1,0	0,9	0,05	247	285
	1,5	1,0	0,06	240	277
	2,0	1,2	0,06	167	193
	2,1	1,2	0,07	194	224

#### SPECIFICATIONS

Pressure: 1 to 2.1 bars\*  
Spacing: 0.9 to 5.5 m

#### MODELS

- 4-VAN Series: 0° Trajectory
- 6-VAN Series: 0° Trajectory
- 8-VAN Series: 5° Trajectory
- 10-VAN Series: 10° Trajectory
- 12-VAN Series: 15° Trajectory
- 15-VAN Series: 23° Trajectory
- 18-VAN Series: 26° Trajectory

##### 6-VAN Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
330°	1,0	1,2	0,19	144	166
	1,5	1,5	0,23	112	129
	2,0	1,8	0,27	91	105
	2,1	1,8	0,27	91	105
270°	1,0	1,2	0,18	167	193
	1,5	1,5	0,21	124	143
	2,0	1,8	0,24	99	114
180°	1,0	1,2	0,10	139	161
	1,5	1,5	0,11	98	113
	2,0	1,8	0,13	80	92
90°	1,0	1,2	0,06	167	193
	1,5	1,5	0,07	124	143
	2,0	1,8	0,08	99	114
	2,1	1,8	0,08	99	114



\*Rain Bird recommends using 1800 spray heads equipped with PRS system to maintain optimum nozzle performance in higher pressure situations.

##### 8-VAN Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
330°	1,0	1,8	0,27	91	105
	1,5	2,1	0,32	79	91
	2,0	2,3	0,38	78	90
	2,1	2,4	0,39	74	86
270°	1,0	1,8	0,25	103	119
	1,5	2,1	0,30	91	105
	2,0	2,3	0,34	86	99
180°	1,0	1,8	0,19	117	135
	1,5	2,1	0,23	104	120
	2,0	2,3	0,26	98	113
90°	1,0	1,8	0,12	148	171
	1,5	2,1	0,14	127	147
	2,0	2,3	0,16	121	140
	2,1	2,4	0,16	111	128

Note: 4-VAN, 6-VAN, 8-VAN Series, Turning the radius reduction screw may be required to achieve catalog radius and flow when the arc is set at less than the maximum arc.

##### 10-VAN Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
360°	1,0	2,1	0,44	96	111
	1,5	2,4	0,53	89	103
	2,0	2,7	0,57	76	88
	2,1	3,1	0,59	63	73
270°	1,0	2,1	0,33	96	111
	1,5	2,4	0,40	89	103
	2,0	2,7	0,43	76	88
180°	1,0	2,1	0,22	96	111
	1,5	2,4	0,27	89	103
	2,0	2,7	0,29	76	88
90°	1,0	2,1	0,11	96	111
	1,5	2,4	0,13	89	103
	2,0	2,7	0,14	76	88
	2,1	3,1	0,17	73	85

##### 12-VAN Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
360°	1,0	2,7	0,40	55	63
	1,5	3,2	0,48	47	54
	2,0	3,6	0,59	46	53
	2,1	3,7	0,60	44	51
270°	1,0	2,7	0,30	55	63
	1,5	3,2	0,36	47	54
	2,0	3,6	0,45	46	53
180°	1,0	2,7	0,20	55	63
	1,5	3,2	0,24	47	54
	2,0	3,6	0,30	46	53
90°	1,0	2,7	0,10	55	63
	1,5	3,2	0,12	47	54
	2,0	3,6	0,15	46	53
	2,1	3,7	0,15	44	51

##### 15-VAN Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
360°	1,0	3,4	0,60	52	60
	1,5	3,9	0,72	47	55
	2,0	4,5	0,84	41	48
	2,1	4,6	0,84	40	46
270°	1,0	3,4	0,45	52	60
	1,5	3,9	0,54	47	55
	2,0	4,5	0,63	41	48
180°	1,0	3,4	0,30	52	60
	1,5	3,9	0,36	47	55
	2,0	4,5	0,42	41	48
90°	1,0	3,4	0,15	52	60
	1,5	3,9	0,18	47	55
	2,0	4,5	0,21	41	48
	2,1	4,6	0,21	40	46

##### 18-VAN Series

Nozzle	bar	m	m <sup>3</sup> /h	■ mm/h	▲ mm/h
360°	1,0	4,3	0,96	52	60
	1,5	4,8	1,07	47	55
	2,0	5,4	1,20	41	48
	2,1	5,5	1,21	40	46
270°	1,0	4,3	0,72	52	60
	1,5	4,8	0,80	47	55
	2,0	5,4	0,90	41	48
180°	1,0	4,3	0,48	52	60
	1,5	4,8	0,54	47	55
	2,0	5,4	0,60	41	48
90°	1,0	4,3	0,24	52	60
	1,5	4,8	0,27	47	55
	2,0	5,4	0,30	41	48
	2,1	5,5	0,30	40	46

